

RUST ACTIVATOR GEL

COMPOSITION

The **RUST ACTIVATOR** is a primer that produces an aging effect by oxidation on metal surfaces.

DIRECTIONS FOR USE

Before applying the rust activator, the surface must be **completely clean** and free of traces of paint, grease or any other substance.

Wear gloves, protective clothing and safety goggles to avoid contact with skin or eyes. Use in well-ventilated areas and do not inhale the vapors.

Apply to the surface to be treated **with a sponge**. On vertical surfaces, take care not to use too much product, to avoid runs.

After **24 hours** the final finish will start to show. If greater oxidation is desired, a further coat of product can be applied.

The appearance of the oxidation will depend on factors such as the method of application and ambient humidity and, if the surface to be treated is exposed outdoors, on rain and the hours of direct sunlight.

TECHNICAL CHARACTERISTICS

Parameter	Result
Appearance:	Yellowish gel
Density:	1 kg/l

STORAGE

Must be stored **between 5 and 40 °C** in its original packaging. Do not store for more than **twelve months**.

SAFETY AND HYGIENE

Slightly corrosive product. Avoid contact with skin and eyes; do not inhale the vapors. In case of skin contact, wash with plenty of water and also wash the clothing worn. In case of eye contact, rinse with plenty of water and seek medical attention if necessary.

PACKAGING

2.5 L plastic bucket.

This information reflects the current state of our knowledge and provides information about our products and their possible applications. Its purpose is therefore not to guarantee specific properties of the products or their suitability for a particular application. Any existing industrial property rights must be respected. Quality control parameters will be detailed in the specification sheet of each product.