

PIGMENTS

COMPOSITION

SATINE offers a color chart of **60 colors** referenced to the NCS chart, with the possibility of making any other color from the chart, suitable for the products developed and marketed.

The pigment system has been formulated to meet the performance needs of the products in both industrial applications and high-end decoration.

They have excellent weather resistance for exterior applications.

They are fully compatible with each other and can be used interchangeably to create a fully customized system.

USES

SATINE pigments can be mixed with each other. Applicable to the whole range of SATINE cement-based products, microcement, etc.

PROPERTIES

Easy to mix with SATINE products, as they are prepared and pre-diluted to make mixing easier.

Complies with the following test methods:

- ISO 2811-1 / ASTM D1475 (density)
- ISO 2555 / ASTM D2196 (viscosity)

PACKAGING

Each pigment has a specific weight in order to achieve the color referenced in the NCS color chart.

COLORS

The SATINE color table is attached. In addition to the referenced colors, any other color from the NCS chart is available on request.

TECHNICAL CHARACTERISTICS

Parameter	Value
Appearance	Liquid
Color	SATINE color chart
Odor	Slight
Boiling point/range	Not determined
Flash point	100 °C
Vapor pressure	Not determined
Density	Approx. 1.23-2.90 g/cm ³
Water solubility	Not determined
Solubility in other solvents	Not determined
Viscosity	± 1200 mPa·s
Composition	Pigment pastes of mineral oxides, water-based

DILUTION

Product for coloring mortars, microcements, etc.

STORAGE

12 months from the date of manufacture, in the original closed container, protected from the weather and moisture.

APPLICATION

SATINE pigments mix perfectly with cement-based products and, above all, for application with microcement, etc. In the case of microcement, the pigments are dosed exactly for the size of the bucket.











For technical and printing reasons, once applied, the colors may show slight differences from the original chart, due to the type of lacquering, different drying time or applied thickness, which will not be grounds for a claim. In addition, the surface appearance and the application method used may cause a difference in perception between the color of the chart and that of the applied surface.

If you need other colors that are not within the range presented in each chart, please contact our sales department. As manufacturers, we can supply any color to your taste.

This information reflects the current state of our knowledge and provides information about our products and their possible applications. Its purpose is therefore not to guarantee specific properties of the products or their suitability for a particular application. Any existing industrial property rights must be respected. Quality control parameters will be detailed in the specification sheet of each product.

SATINESTONE - Carabona Industrial Estate - C/ Coure No. 16, 18 and 20 - 12530 Burriana - Castellón - SPAIN Tel. +34 692 100 100 / +34 969 100 100 Email: info@satine.es

COLOR CHART FOR CEMENT-BASED PRODUCTS

									
S 0500-N	S 1502-Y	S 3000-N	S 5502-B	S 7500-N	S 8500-N	S 0505-Y10R	S 0515-G90Y	S 1010-Y20R	S 1505-Y30R
									
S 2030-Y20R	S 3030-Y20R	S 1020-Y30R	S 1020-Y40R	S 2005-Y40R	S 3010-Y30R	S 4005-Y20R	S 4010-Y10R	S 0502-Y50R	S 1002-Y50R
									
S 1002-R	S 0505-Y70R	S 0510-R	S 2010-Y90R	S 3020-Y70R	S 4010-Y70R	S 4020-Y90R	S 2002-R50B	S 1020-R60B	S 1015-R80B
									
S 0530-R90B	S 3010-B	S 2040-R90B	S 0510-G20Y	S 0907-G60Y	S 1002-G50Y	S 1510-G80Y	S 0530-G50Y	S 3030-G70Y	S 4010-G90Y
									
S 0560-Y	S 1070-Y	S 4050-Y	S 6010-Y50R	S 6005-Y80R	S 3050-Y70R	S 4050-Y80R	S 1080-R	S 1060-R30B	S 2040-R30B

This information reflects the current state of our knowledge and provides information about our products and their possible applications. Its purpose is therefore not to guarantee specific properties of the products or their suitability for a particular application. Any existing industrial property rights must be respected. Quality control parameters will be detailed in the specification sheet of each product.