

PRIMER VARNISH PLUS

DESCRIPTION

PRIMER VARNISH PLUS is a high-quality floor sealer: an extra-fine water-based resin specially designed to penetrate easily without leaving a plastic film on the surface, protecting against moisture, condensation and water stains. Especially suitable before varnishing in bathrooms, kitchens and outdoors. **NOT SUITABLE FOR POOLS.**

Sealing of indoor and outdoor floors with an aliphatic acrylic emulsion, used mainly for the decorative finishing of trafficable floors and for sealing and consolidating substrates.

APPLICATIONS

Any absorbent surface, natural or artificial, that needs to be sealed. Provides a certain gloss or wet effect, which will vary depending on the coverage on each substrate. Where a seamless surface is required, it adapts to the texture of the base substrate while unifying the surface.

Before applying the product, shake well until perfectly homogeneous, either by hand or with a mechanical mixer.

SAFETY AND HYGIENE

PRIMER VARNISH PLUS is not toxic, hazardous or flammable under normal handling conditions. Use without special safety measures is recommended, only the legal occupational health regulations.

PACKAGING

5 L drum. Pallet of 1.15 × 1.15 m, 144 units.



TECHNICAL CHARACTERISTICS

Parameter	Value
Specific weight	1.03 g/cm ³
Dry to the touch	1 hour
Frost resistance	Good
Outdoor resistance	Aliphatic
Abrasion resistance	High
Yellowing	Aliphatic
Saponification resistance	Very good
Adhesion	Clean, dry porous surfaces
Finish	Silky matt
Minimum thickness per coat	Impregnating
Coverage	± 12-15 m ² /kg, depending on the surface

SUBSTRATE PREPARATION AND APPLICATION

- The surface must be leveled, clean and free of dust, grease and foreign substances.
- If a second coat is applied, make sure the previous coat is completely dry.
- The drying time for each coat is approximately **24 hours**, depending on temperature and ambient relative humidity.
- During the drying time of each coat, the treated area must not get wet or be opened to use.
- Do not apply the product in adverse weather conditions: cold weather, rain, etc.
- The ambient temperature for application and curing must be between **6 and 35 °C**.

STORAGE

Store between **5 and 40 °C** in the original packaging. Do not store for more than **12 months**.

DILUTION

Ready to use. Depending on the porosity, nature and characteristics of the substrate, as well as the requirements of the finishing product, it can be diluted over a wide range. PRIMER VARNISH PLUS : water = **1:2, 1:3, 1:4, 1:5**.

This information reflects the current state of our knowledge and provides information about our products and their possible applications. Its purpose is therefore not to guarantee specific properties of the products or their suitability for a particular application. Any existing industrial property rights must be respected. Quality control parameters will be detailed in the specification sheet of each product.