

RESIN FILLER

DESCRIPTION

Two-component polyester resin, solvent-free, fluid and transparent, for repair, coating and lamination.

PROPERTIES

- The resin hardens on the surface exposed to air.
- **High strength, high bonding power.**
- Very water-resistant, low water absorption.
- Low material loss during hardening.
- Solvent-free, so there is almost no odor nuisance.
- Resistant to weak acids and alkalis, inorganic salt solutions, gasoline, petroleum, grease and oils.
- Can be applied even at relatively low temperatures (**min. 10 °C**).

SUBSTRATE PREPARATION AND APPLICATION

The base surface must be clean and free of dust, grease and foreign substances.

Pre-treatment:

No primer is required beforehand. **The surface must be dry.**

Application:

Accurately dose components A and B (resin and hardener) and mix them thoroughly. The mixture is then ready for use.

Apply with a brush, roller or spatula onto the surface to be treated.

The working time is approx. **30 min** at +18 to 25 °C.

In most cases, two coats are applied to achieve sufficient coat thickness.

DISPOSAL AND ENVIRONMENT

Take all necessary measures to avoid waste production as far as possible. Analyze possible recovery or recycling methods. Do not pour into drains or into the environment. Dispose of at an authorized waste collection point.

Waste must be handled and disposed of in accordance with current local/national legislation. Empty containers and packaging must be disposed of in accordance with current legislation.

Neutralization or destruction of the product must be carried out by controlled incineration in special chemical waste plants, in accordance with local regulations.

FIELDS OF APPLICATION

- For repair, bonding or coating of porous or smooth surfaces.
- As a resin for embedding coatings and glass-fiber-reinforced parts.
- As a putty for connections and other cavities.
- Coating of concrete floors.
- Repair of molded parts.

STORAGE

- Store in accordance with local regulations.
- Store in a separate, approved area.
- Store in the original container, protected from direct sunlight, in a dry, cool and well-ventilated area, away from incompatible materials, food and drink. **Keep locked up.**
- Eliminate all sources of ignition.
- Keep away from oxidizing materials.
- Keep the container tightly closed and sealed until use. Opened containers must be carefully resealed and kept upright to prevent leakage.
- Do not store in unlabeled containers.
- Avoid environmental contamination. Dispose of in accordance with local regulations.

IMPORTANT NOTES AND RECOMMENDATIONS

RESIN FILLER must be applied with good ventilation and with the necessary protective measures. Protect containers from high temperatures and direct sunlight. **Do not eat, drink or smoke** during application. In case of eye contact, rinse with plenty of clean water. **Toxic if swallowed.** Keep out of the reach of children.

PACKAGING

RESIN FILLER comes in a **3 kg + 60 g** pack.

This information reflects the current state of our knowledge and provides information about our products and their possible applications. Its purpose is therefore not to guarantee specific properties of the products or their suitability for a particular application. Any existing industrial property rights must be respected. Quality control parameters will be detailed in the specification sheet of each product.