

RESINA PRESS

COMPOSITION

RESINA PRESS is a binder in aqueous dispersion, free of organic solvents and bituminous products.

APPLICATIONS

RESINA PRESS is designed for surface preparation and is especially intended to consolidate substrates that require it. It also optimizes anchoring or compaction of substrates and considerably increases the flexural strength of the product.

SAFETY AND HYGIENE

RESINA PRESS is **not toxic, hazardous or flammable** under normal handling conditions.

Use without special safety measures is recommended; only the legal occupational health regulations apply.

PACKAGING

5 L jerrycan

Pallet: 1.15 x 1.15 - 144 units

TECHNICAL CHARACTERISTICS

Specific gravity at 20 °C:	1.03-1.06 g/cm ³
Density:	0.98 g/cm ³
pH:	4.0
Color:	Milky
Solids content:	21 %

STORAGE

Must be stored **between 5 and 40 °C** in its original package. Do not store for more than **twelve months**.

DILUTION

READY TO USE.

Depending on the porosity, nature and characteristics of the substrate, as well as the requirements of the finishing product, it can be used **undiluted or diluted 1/1** with tap water.

This information reflects the current state of our knowledge and provides information about our products and their possible applications. Its purpose is therefore not to guarantee specific properties of the products or their suitability for a particular application. Any existing industrial property rights must be respected. Quality control parameters will be detailed in the specification sheet of each product.

SATINESTONE - Carabona Industrial Estate - C/ Coure No. 16, 18 and 20 - 12530 Burriana - Castellón - SPAIN Tel. +34 692 100 100 / +34 969 100 100 Email: info@satine.es