

Black Label Component B

Page 1 of 12

Version 1 Issue date: 14/06/2011

Version 91 (replaces version 90) Revision date: 08/02/2024 Print date: 12/09/2024

1

IDENTIFICATION OF THE SUBSTANCE OR THE MIXTURE AND OF THE COMPANY OR THE UNDERTAKING.

1.1 Product identifier.

Product name:	Black Label Component B
---------------	-------------------------

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Coating

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	SATINE FACTORY SL
Address:	C/Coure, 16-18.
Town:	12530 Burriana
Province:	Castellón.
Telephone:	+34 692 100 100
E-mail:	info@satine.es
Web:	www.satine.es

1.4 Emergency telephone number:

+34 977 822 245 (Only available during office hours; Monday-Friday; 08:00-18:00)

2

HAZARDS IDENTIFICATION.

IRRITANT PREPARATION. Splashes in the eyes may cause irritation.

2.1 Classification of the substance or mixture.

According to Regulation (EC) No 1272/2008:

- Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.
- Eye Irrit. 2 : Causes serious eye irritation.
- Muta. 2 : Suspected of causing genetic defects.
- Skin Irrit. 2 : Causes skin irritation.
- Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements. Labelling according to Regulation (EC) No 1272/2008:

Pictograms:



Signal word:

Warning

Hazard statements:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:

P201	Obtain special instructions before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection
P321	Specific treatment (see supplemental first aid instructions on this label)
P391	Collect spillage.
P501	Dispose of contents or container to (in accordance with local, regional, national or international regulations)

Supplemental hazard statements:

EUH205	Contains epoxy constituents. May produce an allergic reaction.
--------	--

Contains:

- reaction product: bisphenol-A-(epichlorohydrin), epoxy resin (number average molecular weight ≤ 700)
2,3-epoxypropyl o-tolyl ether

2.3 Other hazards.

The mixture does not contain substances classified as PBT (Persistent, Bioaccumulative and Toxic).

The mixture does not contain substances classified as vPvB (very Persistent and very Bioaccumulative).

The mixture does not contain substances with endocrine-disrupting properties.

Under normal conditions of use and in its original form, the product has no other adverse effects on health or the environment.

3

COMPOSITION/INFORMATION ON INGREDIENTS.

IRRITANT PREPARATION. Splashes in the eyes may cause irritation.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances that represent a hazard to health or the environment in accordance with Regulation (EC) No. 1272/2008, that have been assigned a Community workplace exposure limit, that are classified as PBT/vPvB or that are included in the Candidate List:

				(*)Classification - Regulation 1272/2008	
				Classification	Specific concentration limits and Acute Toxicity Estimate
Index No.: 603-074-00-8 CAS No.: 25068-38-6 EC No.: 500-033-5 Registration No.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorohydrin), epoxy resin (number average molecular weight ≤ 700)	25 - 100 %		Aquatic Chronic 2, H411 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	Eye Irrit. 2, H319: C ≥ 5 % Skin Irrit. 2, H315: C ≥ 5 %
Index No.: 603-056-00-X CAS No.: 2210-79-9 EC No.: 218-645-3	2,3-epoxypropyl o-tolyl ether	25 - 50 %		Aquatic Chronic 2, H411 - Muta. 2, H341 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

(*) The full text of the H phrases is detailed in section 16 of this Safety Data Sheet.

4

FIRST AID MEASURES.

IRRITANT MIXTURE. Repeated or prolonged contact with the skin or mucous membranes may cause irritant symptoms such as redness, blistering or dermatitis. Some of the symptoms may not be immediate. Allergic skin reactions may occur.

4.1 Description of first aid measures.

In case of doubt, or when symptoms of discomfort persist, seek medical attention. Never give anything by mouth to unconscious persons.

Inhalation.

Move the casualty to fresh air, keep them warm and at rest; if breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and easy to do. Rinse the eyes thoroughly with clean, fresh water for at least 10 minutes, pulling the eyelids upwards, and seek medical attention. Do not allow the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash the skin vigorously with soap and water or a suitable skin cleanser. NEVER use solvents or thinners.

Ingestion.

If swallowed accidentally, seek medical attention immediately. Keep at rest. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant product: repeated or prolonged contact with the skin or mucous membranes may cause redness, blistering or dermatitis; inhalation of spray mist or suspended particles may cause irritation of the respiratory tract; some of the symptoms may not be immediate.

Long-term exposure (chronic) may cause damage to certain organs or tissues.

May cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt, or if symptoms of discomfort persist, seek medical attention. Never give anything by mouth to unconscious persons. Keep the person comfortable. Turn them onto their left side and keep them there while awaiting medical help.

5 FIRE-FIGHTING MEASURES.

The product does not present any particular fire hazard.

5.1 Extinguishing media. Suitable extinguishing media:

Extinguishing powder or CO₂. In the case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct jet of water for extinguishing. In the presence of electrical voltage, the use of water or foam as extinguishing media is not acceptable.

5.2 Special hazards arising from the substance or mixture. Special risks.

Exposure to combustion or decomposition products may be harmful to health.

5.3 Advice for fire-fighters.

Cool tanks, cisterns or containers close to the source of heat or fire with water. Take the wind direction into account. Prevent the products used in fire-fighting from entering drains, sewers or watercourses. Residues of product and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

Depending on the magnitude of the fire, it may be necessary to use heat-protective suits, self-contained breathing apparatus, gloves, protective goggles or face masks and boots.

6 ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and personal protection measures, see section 8.

6.2 Environmental precautions.

Product hazardous to the environment; in case of large spills or if the product contaminates lakes, rivers or sewers, inform the competent authorities in accordance with local legislation. Avoid contamination of drains, surface or ground water, as well as soil.

6.3 Methods and material for containment and cleaning up.

Contain and collect the spill with inert absorbent material (earth, sand, vermiculite, diatomaceous earth...) and clean the area immediately with a suitable decontaminant.

Place the residues in closed containers suitable for disposal, in accordance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and personal protection measures, see section 8.

For waste disposal, follow the recommendations of section 13.

7 HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

Smoking, eating and drinking must be prohibited in the application area.

Comply with legislation on occupational safety and hygiene.

Never use pressure to empty the containers; they are not pressure-resistant. Keep the product in containers of the same material as the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store in accordance with local legislation. Observe the indications on the label. Store the containers between 5 and 25 °C, in a dry, well-ventilated place, away from sources of heat and direct sunlight. Keep away from ignition points. Keep away from oxidising agents and strongly acidic or alkaline materials. Do not smoke. Prevent entry by unauthorised persons. Once opened, the containers must be carefully resealed and placed upright to avoid spillage.

Classification and storage threshold quantity in accordance with Annex I of Directive 2012/18/EU (SEVESO III):

Code	Description	Threshold quantity (tonnes) for the application of	
		lower-tier requirements	upper-tier requirements
E2	ENVIRONMENTAL HAZARDS - Hazardous to the aquatic environment, chronic category 2	200	500

7.3 Specific end use(s).

Not available.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

The product does NOT contain substances with Occupational Exposure Limit Values. The product does NOT contain substances with Biological Limit Values.

DNEL/DMEL concentration levels:

Name	DNEL/DMEL	Type	Value
reaction product: bisphenol-A-(epichlorohydrin), epoxy resin (number average molecular weight ≤ 700) CAS No.: 25068-38-6 EC No.: 500-033-5	DNEL (Workers)	Inhalation, Chronic, Systemic effects	12,25 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which no adverse effects are expected.

DMEL: Derived Minimal Effect Level, level of exposure corresponding to a low risk, which should be considered a minimal tolerable risk.

8.2 Exposure controls.

Technical measures:

Provide adequate ventilation, which can be achieved by good local extraction-ventilation and a good general extraction system.

Concentration:	100 %
Uses:	Coating
Respiratory protection:	
PPE: Filter mask for protection against gases and particles Characteristics: «CE» marking, Category III. The mask must have a wide field of vision and an anatomical shape to provide a tight and hermetic seal. CEN standards: EN 136, EN 140, EN 405 Maintenance: Do not store in places exposed to high temperatures or humid environments before use. The condition of the inhalation and exhalation valves of the face adapter must be checked in particular. Remarks: The manufacturer's instructions on the use and maintenance of the equipment must be read carefully. The necessary filters shall be fitted to the equipment according to the specific characteristics of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), and changed as advised by the manufacturer. Type of filter required: A2	
Hand protection:	

PPE: Protective gloves against chemicals

Characteristics: «CE» marking, Category III.

CEN standards: EN 374-1, EN 374-2, EN 374-3, EN 420

Maintenance: Store in a dry place, away from possible heat sources, and avoid exposure to sunlight as far as possible. No modifications that could alter their resistance shall be made to the gloves, and no paints, solvents or adhesives shall be applied.

Remarks: Gloves must be the correct size and fit the hand without being too loose or too tight. They must always be used with clean, dry hands.

PVC (Polyvinyl
Material: chloride)

Breakthrough
> 480 time (min.):

Material
0.35 thickness (mm):

Eye protection:

PPE: Full-frame protective goggles

Characteristics: «CE» marking, Category II. Full-frame eye protector for protection against liquid splashes, dust, fumes, mists and vapours.

CEN standards: EN 165, EN 166, EN 167, EN 168

Maintenance: Visibility through the lenses must be optimal, so they must be cleaned daily; the protectors must be disinfected periodically following the manufacturer's instructions.

Remarks: Signs of deterioration may include: yellowing of the lenses, surface scratches on the lenses, tears, etc.

Skin protection:

PPE: Protective clothing with antistatic properties

Characteristics: «CE» marking, Category II. Protective clothing must not be tight or loose so that it does not interfere with the wearer's movements.

CEN standards: EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5

Maintenance: The washing and care instructions provided by the manufacturer must be followed to ensure consistent protection.

Remarks: Protective clothing should provide a level of comfort consistent with the level of protection it must provide against the risk concerned, the environmental conditions, the wearer's activity level and the expected duration of use.

PPE: Protective footwear with antistatic properties

Characteristics: «CE» marking, Category II.

CEN standards: EN ISO 13287, EN ISO 20344, EN ISO 20346

Maintenance: Footwear must be checked regularly; if its condition is poor, it must no longer be used and must be replaced.

Remarks: Comfort in use and acceptability are factors that are assessed very differently by individuals. It is therefore advisable to try different models of footwear and, if possible, different widths.

9

PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Not applicable/Not available due to the nature/properties of the product.

Colour: amarillo claro

Odour: ligero

Odour threshold: Not applicable/Not available due to the nature of the product/properties of the product.

Melting point: nd °C

Freezing point: Not applicable/Not available due to the nature of the product/properties of the product.

Boiling point/Initial boiling point/boiling range: 220 °C

Flammability: no inflamable

Lower explosion limit: nd

Upper explosion limit: Not applicable/Not available due to the nature of the product/properties of the product.

Flash point: 138 °C

Auto-ignition temperature: Not applicable/Not available due to the nature of the product/properties of the product.

Decomposition temperature: Not applicable/Not available due to the nature of the product/properties of the product.

pH: nd

Kinematic viscosity: nd

Solubility: nd

Water solubility: not soluble

Fat solubility: nd

Partition coefficient (n-octanol/water)(logarithmic value): nd

Vapour pressure: 1 Pa

Absolute density: Not applicable/Not available due to the nature of the product/properties of the product.

Relative density: 1.14

Vapour density: nd

Particle characteristics: Not applicable/Not available due to the nature of the product/properties of the product.

9.2 Other data. Information on physical hazard classes

Explosives:

- Explosive properties: nd

Other safety characteristics

Viscosity: 100-650

Dropping point: nd

Flash: nd

10

STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards due to its reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present the possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any type of incorrect handling.

10.5 Incompatible materials.

Keep away from oxidising agents and strongly alkaline or acidic materials, in order to avoid exothermic reactions.

10.6 Hazardous decomposition products.

Does not decompose if used for the intended purposes.

11

TOXICOLOGICAL INFORMATION.

Based on the properties of the epoxy components and taking into account the toxicological data of similar preparations, this preparation may sensitise and irritate the skin, eyes and respiratory tract.

Low molecular weight epoxy components are irritating to the eyes, mucous membranes and skin. Repeated skin contact may lead to irritation or sensitisation, possibly with marked self-sensitisation to other epoxies.

IRRITANT MIXTURE. Splashes in the eyes may cause irritation.

IRRITANT MIXTURE. Repeated or prolonged contact with the skin or mucous membranes may cause irritant symptoms such as redness, blistering or dermatitis. Some of the symptoms may not be immediate. Allergic skin reactions may occur.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008.

No tested data available on the product.

Repeated or prolonged contact with the product may cause defatting of the skin, resulting in non-allergic contact dermatitis, and absorption of the product through the skin.

a) acute toxicity;

Inconclusive data for classification.

b) skin corrosion or irritation;

Classified product:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage or irritation;

Classified product:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Classified product:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Classified product:

Mutagen, Category 2: Suspected of causing genetic defects.

f) carcinogenicity;

Inconclusive data for classification.

g) reproductive toxicity;

Inconclusive data for classification.

h) specific target organ toxicity (STOT) - single exposure;

Inconclusive data for classification.

i) specific target organ toxicity (STOT) - repeated exposure;

Inconclusive data for classification.

j) aspiration hazard;

Inconclusive data for classification.

11.2 Information on other hazards.

Endocrine-disrupting properties.

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information.

No other information is available on other adverse effects on health.

12

ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available on the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available on the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available on the persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available on the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available on mobility in soil.

The product must not be allowed to enter sewers or watercourses.

Avoid penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available on the PBT and vPvB assessment of the product.

12.6 Endocrine-disrupting properties.

This product does not contain components with endocrine-disrupting properties on the environment.

12.7 Other adverse effects.

The product is not affected by Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No other information is available on other adverse effects on the environment.

13

DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Discharge into sewers or watercourses is not permitted. Waste and empty containers must be handled and disposed of in accordance with the local/national legislation in force.

Follow the provisions of Directive 2008/98/EC regarding waste management.

14

TRANSPORT INFORMATION.

Transport in accordance with ADR/TPC regulations for road transport, RID for rail, IMDG for sea and ICAO/IATA for air transport.

Land: Road transport: ADR, Rail transport: RID.

Transport documentation: Consignment note and Written instructions.

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading.

Air: Transport by aircraft: IATA/ICAO.

Transport document: Air waybill.

14.1 UN number or ID number.

UN No.: UN3082

14.2 UN proper shipping name.

Description:

ADR/RID: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT $\leq$ 700) / 2,3-EPOXYPROPYL O-TOLYL ETHER), 9, PG III, (-)

IMDG: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT $\leq$ 700) / 2,3-EPOXYPROPYL O-TOLYL ETHER), 9, PG/E III, MARINE POLLUTANT

ICAO/IATA:

UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS REACTION PRODUCT: BISPHENOL-A-(EPICHLOROHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT $\leq$ 700) / 2,3-EPOXYPROPYL O-TOLYL ETHER), 9, PG III

14.3 Transport hazard class(es).

Class(es): 9

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: Yes



Environmentally hazardous

Transport by ship, EmS - Emergency schedules (F - Fire, S - Spillage): F-A,S-F

14.6 Special precautions for user.

Labels: 9



Hazard number: 90

Provisions concerning bulk transport in ADR: Bulk transport not authorised under ADR.

Act in accordance with section 6.

ADR limited quantity: 5 L

IMDG limited quantity: 5 L

ICAO limited quantity: 30 kg B

14.7 Maritime transport in bulk according to IMO instruments.

The product is not affected by bulk shipment on ships.

15

REGULATORY INFORMATION.

This information is given in this Safety Data Sheet of the Preparation.

15.1 Regulations/legislation specific for the substance or mixture on safety, health and environment.

Volatile organic compound (VOC)

Product subcategory (Directive 2004/42/EC): j - Two-pack reactive performance coatings for specific end uses such as floors, water-based

Phase I * (from 01/01/2007): 140 g/l

Phase II* (from 01/01/2010): 140 g/l

(*) g/l ready to use

VOC content (w/w): 0.5 %

VOC content: 2 g/l

The provisions of Directive 2004/42/EC on VOCs apply to this product. See the product label and/or safety data sheet for more information.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established in Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals.

Restrictions on the manufacture, placing on the market and use of certain dangerous substances and mixtures:

Name of the substance, group of substances or mixtures	Restrictions
--	--------------

3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories laid down in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6, 2.7, 2.8 (types A and B), 2.9, 2.10, 2.12, 2.13 (categories 1 and 2), 2.14 (categories 1 and 2), 2.15 (types A to F); (b) hazard classes 3.1 to 3.6, 3.7 (adverse effects on sexual function and fertility or on development), 3.8 (effects other than narcotic effects), 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.

1. Shall not be used in: - decorative articles intended to produce light or colour effects by means of different phases, for example in ambient lamps and ashtrays, - tricks and jokes, - games for one or more participants or any article intended to be used as such, even with decorative aspects. 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or a perfuming agent, or both, if: - they can be used as fuel in decorative oil lamps intended to be supplied to the general public, and - they present an aspiration hazard and are labelled with H304. 4. Decorative oil lamps intended to be supplied to the general public shall not be placed on the market unless they conform to the European Standard on decorative oil lamps (EN 14059) adopted by the European Committee for Standardization (CEN). 5. Without prejudice to the implementation of other Community provisions on the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: (a) lamp oils labelled with H304 and intended to be supplied to the general public shall be visibly, legibly and indelibly marked with the following: «Keep lamps filled with this liquid out of the reach of children»; and, by 1 December 2010: «Just a sip of lamp oil – or even sucking the lamp wick – may lead to life-threatening lung damage»; (b) by 1 December 2010, grill lighter fluids labelled with H304 and intended to be supplied to the general public shall be legibly and indelibly marked with the following: «Just a sip of grill lighter fluid may lead to life-threatening lung damage»; (c) by 1 December 2010, lamp oils and grill lighter fluids labelled with H304 and intended to be supplied to the general public shall be packaged in black opaque containers not exceeding 1 litre in capacity.

15.2 Chemical safety assessment.

A chemical safety assessment of the product has not been carried out.

16

OTHER INFORMATION.

Full text of the H phrases appearing in section 3:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Chronic 2 : Chronic effects on the aquatic environment, Category 2

Eye Irrit. 2 : Eye irritation, Category 2

Muta. 2 : Mutagen, Category 2

Skin Irrit. 2 : Skin irritant, Category 2

Skin Sens. 1 : Skin sensitiser, Category 1

Classification and procedure used to derive the classification of mixtures in accordance with Regulation (EC) No 1272/2008 [CLP]:

Physical hazards	According to test data
Health hazards	Calculation method
Environmental hazards	Calculation method

Basic training in occupational health and safety is advised in order to handle the product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, level of exposure corresponding to a low risk, which should be considered a minimal tolerable risk.

DNEL: Derived No Effect Level, level of exposure to the substance below which no adverse effects are expected.

PPE: Personal protective equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Dangerous Goods Code.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

Main bibliographic references and data sources:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information provided in this Safety Data Sheet has been drawn up in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

The information in this Product Safety Data Sheet is based on current knowledge and on the laws in force of the EC and of the Member States, insofar as the working conditions of users are beyond our knowledge and control. The product must not be used for purposes other than those specified, without first obtaining written instructions for its handling. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established in legislation.